

Multi M1

-0.693147181 30		N ₂ Tissue Compartments										
Copyright (C) 1998 Benton P. Zwart		5	10	20	40	80	120	160	320	480	640	T1/2
Initial Tissue PN ₂	21.782	2.2990	2.0083	1.7060	1.3905	1.2726	1.2619	1.2548	1.2350	1.2208	1.2137	Slope
Safety Enhancement (20-100)	20	103.60	87.58	72.42	58.08	52.08	50.83	48.33	47.24	46.74	46.24	Intercept
Local Barometer (mmHg)	635	1.9968	1.7642	1.5224	1.2700	1.1757	1.1671	1.1614	1.1456	1.1342	1.1285	Safety Slope
Initial Steady State FiO ₂	0.21	88.08	75.26	63.14	51.66	46.86	45.86	43.86	42.99	42.59	42.19	Safety Intercept
Depth Gauge Must = 0 at Surface of Water!												
Linear Transition Time	0.00	2.3	21.78	21.78	21.78	21.78	21.78	21.78	21.78	21.78	21.78	PN ₂ (t)
Transition O ₂ Fraction	0.21											
Calculated Target PN ₂	72.342	238.39	205.31	172.42	139.58	126.67	124.79	121.86	119.61	118.28	117.36	Nxt Seg Ms
Initial PN ₂ Inspired	21.782	205.14	178.68	152.37	126.10	115.76	114.26	111.92	110.12	109.05	108.32	Safety Ms
Target - Initial	50.56	183.36	156.90	130.59	104.31	93.98	92.48	90.14	88.33	87.27	86.53	Buffer
Segment 1 Conditions												
Segment Depth (FSW)	64	71.15	64.56	52.51	40.68	32.33	29.08	27.36	24.65	23.72	23.24	PN ₂ (t)
Segment Time (Min)	27	125.92	107.04	88.93	71.53	64.37	63.01	60.42	59.13	58.50	57.93	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	107.44	92.34	77.85	63.93	58.21	57.12	55.04	54.02	53.51	53.05	Safety Ms
Calculated PN ₂	72.342	36.30	27.78	25.35	23.26	25.88	28.03	27.68	29.36	29.79	29.81	Buffer
58.57												
Linear Transition Time	1.60	1.6										
Transition O ₂ Fraction	0.21	66.60	63.07	52.46	40.99	32.61	29.30	27.54	24.75	23.78	23.29	PN ₂ (t)
Calculated Target PN ₂	33.632	40.84	29.28	25.40	22.94	25.60	27.82	27.50	29.26	29.72	29.76	Buffer
Initial PN ₂ Inspired	72.342											
Target - Initial	-38.71											
Segment 2 Conditions												
Segment Depth (FSW)	15	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Segment Time (Min)	3	90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	33.632	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer
9.57												
Linear Transition Time	0.00	0.5										
Transition O ₂ Fraction	0.21	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Calculated Target PN ₂	21.782	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer
Initial PN ₂ Inspired	33.632											
Target - Initial	-11.85											
Segment 3 Conditions												
Segment Depth (FSW)	0	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Segment Time (Min)	0	90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.782	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer
-5.43												
Linear Transition Time	0.00	0.0										
Transition O ₂ Fraction	0.21	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Calculated Target PN ₂	21.782	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer
Initial PN ₂ Inspired	21.782											
Target - Initial	0											
Segment 4 Conditions												
Segment Depth (FSW)	0	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Segment Time (Min)	0	90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.782	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer
-5.43												
Linear Transition Time	0.00	0.0										
Transition O ₂ Fraction	0.21	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Calculated Target PN ₂	21.782	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer

Multi M1

Initial PN₂ Inspired 21.782
Target - Initial 0

Segment 5 Conditions

Segment Depth (FSW)	0	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Segment Time (Min)	0	90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.782	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer

-5.43

Linear Transition Time 0.00 0.0
Transition O₂ Fraction 0.21
Calculated Target PN₂ 21.782 21.29 7.71 3.95 3.90 7.64 9.97 9.80 11.83 12.48 12.62
Initial PN₂ Inspired 21.782
Target - Initial 0

Segment 6 Conditions

Segment Depth (FSW)	0	55.38	57.54	50.60	40.62	32.63	29.38	27.62	24.81	23.83	23.32	PN ₂ (t)
Segment Time (Min)	0	90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.782	21.29	7.71	3.95	3.90	7.64	9.97	9.80	11.83	12.48	12.62	Buffer

-5.43

Linear Transition Time 0.00 0.0
Transition O₂ Fraction 0.21
Calculated Target PN₂ 21.782 21.29 7.71 3.95 3.90 7.64 9.97 9.80 11.83 12.48 12.62
Initial PN₂ Inspired 21.782
Target - Initial 0

Final Depth (FSW) 0

Final Air PN₂ 21.8 Torr Estimator: Alt (0-20000') = 6200 Torr = 601.77 Equiv = -6.87 FSW

Total Dive Time (Min) 31.6

Residual PN₂ (mm-min) 7504.8 168.001 357.58 576.307 753.45 868.14 911.17 933.682 968.758 980.811 986.907

Residual PN₂ Index (mm) 4.0026

-5.43

Multi M2

-0.693147181		30	N ₂ Tissue Compartments										
RNT for Seg1 Depth	21.8		5	10	20	40	80	120	160	320	480	640	T1/2
Surface Interval (Min)	83		2.2990	2.0083	1.7060	1.3905	1.2726	1.2619	1.2548	1.2350	1.2208	1.2137	Slope
Safety Enhancement (20-100)	20		103.60	87.58	72.42	58.08	52.08	50.83	48.33	47.24	46.74	46.24	Intercept
Local Barometer (mmHg)	635		1.9968	1.7642	1.5224	1.2700	1.1757	1.1671	1.1614	1.1456	1.1342	1.1285	Safety Slope
Surface Interval FiO2	0.21		88.08	75.26	63.14	51.66	46.86	45.86	43.86	42.99	42.59	42.19	Safety Intercept
			26.48	73.13	Depth Gauge Must = 0 at Surface of Water!								
RNT Loading			70.62	61.77	48.98	37.91	30.61	27.85	26.40	24.43	23.65	23.22	
Linear Transition Time	0.00	2.2	70.62	61.77	48.98	37.91	30.61	27.85	26.40	24.43	23.65	23.22	PN ₂ (t)
Transition O ₂ Fraction	0.21												
Calculated Target PN ₂	73.13		240.69	207.32	174.13	140.97	127.94	126.05	123.11	120.84	119.50	118.57	Nxt Seg Ms
Initial PN ₂ Inspired	21.78		207.14	180.44	153.89	127.37	116.94	115.43	113.08	111.26	110.18	109.45	Safety Ms
Target - Initial	51.35		136.52	118.67	104.91	89.45	86.33	87.58	86.68	86.83	86.53	86.22	Buffer
Segment 1 Conditions			Enter Segment Time Only! I Have Already Added The RNT!!										
Segment Depth (FSW)	65		73.03	70.83	62.25	49.49	38.29	33.48	30.83	26.79	25.27	24.45	PN ₂ (t)
Segment Time (Min)	23	45	125.92	107.04	88.93	71.53	64.37	63.01	60.42	59.13	58.50	57.93	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	TBT	107.44	92.34	77.85	63.93	58.21	57.12	55.04	54.02	53.51	53.05	Safety Ms
Calculated PN ₂	73.13		34.41	21.52	15.61	14.44	19.92	23.64	24.21	27.22	28.24	28.60	Buffer
59.57													
Linear Transition Time	1.70	1.7											
Transition O ₂ Fraction	0.21		67.85	68.57	61.65	49.58	38.50	33.67	31.00	26.89	25.34	24.50	PN ₂ (t)
Calculated Target PN ₂	33.63		39.59	23.78	16.20	14.35	19.70	23.44	24.05	27.12	28.17	28.55	Buffer
Initial PN ₂ Inspired	73.13												
Target - Initial	-39.5												
Segment 2 Conditions													
Segment Depth (FSW)	15		35.25	41.24	46.70	44.53	37.66	33.67	31.24	27.21	25.59	24.72	PN ₂ (t)
Segment Time (Min)	22		90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21		76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	33.63		41.42	24.02	7.84	(0.00)	2.62	5.67	6.18	9.44	10.71	11.22	Buffer
9.57													
Linear Transition Time	0.50	0.5											
Transition O ₂ Fraction	0.21		34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Calculated Target PN ₂	21.78		41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer
Initial PN ₂ Inspired	33.63												
Target - Initial	-11.85												
Segment 3 Conditions													
Segment Depth (FSW)	0		34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Segment Time (Min)	0		90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21		76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.78		41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer
-5.43													
Linear Transition Time	0.00	0.0											
Transition O ₂ Fraction	0.21		34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Calculated Target PN ₂	21.78		41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer
Initial PN ₂ Inspired	21.78												
Target - Initial	0												
Segment 4 Conditions													
Segment Depth (FSW)	0		34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Segment Time (Min)	0		90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21		76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.78		41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer
-5.43													
Linear Transition Time	0.00	0.0											
Transition O ₂ Fraction	0.21		34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Calculated Target PN ₂	21.78		41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer
Initial PN ₂ Inspired	21.78												
Target - Initial	0												

Multi M2

Segment 5 Conditions

Segment Depth (FSW)	0	34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Segment Time (Min)	0	90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.78	41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer

-5.43

Linear Transition Time	0.00	0.0										
Transition O ₂ Fraction	0.21	34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Calculated Target PN ₂	21.78	41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer
Initial PN ₂ Inspired	21.78											
Target - Initial	0											

Segment 6 Conditions

Segment Depth (FSW)	0	34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Segment Time (Min)	0	90.41	76.14	62.75	50.22	44.92	43.75	41.34	40.37	39.95	39.49	Nxt Seg Ms
Inspired O ₂ Fraction	0.21	76.68	65.25	54.54	44.52	40.28	39.34	37.42	36.64	36.30	35.94	Safety Ms
Calculated PN ₂	21.78	41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer

-5.43

Linear Transition Time	0.00	0.0										
Transition O ₂ Fraction	0.21	34.71	40.77	46.38	44.38	37.62	33.65	31.23	27.21	25.60	24.72	PN ₂ (t)
Calculated Target PN ₂	21.78	41.96	24.49	8.17	0.14	2.66	5.69	6.19	9.44	10.71	11.22	Buffer
Initial PN ₂ Inspired	21.78											
Target - Initial	0											

Final Depth (FSW)

Final Air PN ₂	21.8	Torr Estimator:	Alt (0-20000') =	16500	Torr =	403.66	Equiv =	-15.47	FSW			
Total Dive Time (Min)	47.2											
Residual PN ₂ (mm-min)	11300	64.6472	189.83	491.857	903.889	1266.69	1424.26	1511.58	1735.69	1830.67	1880.97	
Residual PN ₂ Index (mm)	6.027											

-5.43

Deco Time Estimate (Tot-Seg1) 24.2

Copyright (C) 1998 Benton P. Zwart